



US 20180030745A1

(19) **United States**

(12) **Patent Application Publication**  
**Dinmore et al.**

(10) **Pub. No.: US 2018/0030745 A1**

(43) **Pub. Date: Feb. 1, 2018**

(54) **STAY-IN-PLACE FORMS AND METHODS AND EQUIPMENT FOR INSTALLATION THEREOF**

*E01D 19/12* (2006.01)  
*E04G 11/36* (2006.01)  
*E04G 9/02* (2006.01)

(71) Applicant: **Precasteel, LLC**, Skillman, NJ (US)

(52) **U.S. Cl.**  
CPC ..... *E04G 17/14* (2013.01); *E04G 11/365* (2013.01); *E01D 21/10* (2013.01); *E04G 9/02* (2013.01); *E01D 19/10* (2013.01); *E01D 19/125* (2013.01); *B28B 7/0029* (2013.01); *E01F 15/083* (2013.01)

(72) Inventors: **Gary Michael Dinmore**, Skillman, NJ (US); **John Stanley Deerkoski**, Warwick, NY (US)

(73) Assignee: **Precasteel, LLC**, Skillman, NJ (US)

(57) **ABSTRACT**

(21) Appl. No.: **15/728,085**

(22) Filed: **Oct. 9, 2017**

**Related U.S. Application Data**


(63) Continuation-in-part of application No. 14/099,510, filed on Dec. 6, 2013, now Pat. No. 9,783,982.

(60) Provisional application No. 61/734,418, filed on Dec. 7, 2012.

**Publication Classification**

(51) **Int. Cl.**  
*E04G 17/14* (2006.01)  
*E01D 21/10* (2006.01)  
*B28B 7/00* (2006.01)  
*E01D 19/10* (2006.01)

Stay-in-place forms and methods and equipment for installing thereof. A concrete form includes a vertical component and a horizontal component, the vertical component located substantially perpendicular to the horizontal component. Also, the form includes an interior surface, at least a portion of the interior surface providing a form for supporting uncured concrete; wherein the uncured concrete forms a concrete structural portion upon curing of the uncured concrete; and wherein the interior surface remains attached to the concrete structural portion after curing. The form may include inserts and compatible form attachments. Also, forms including recesses may be utilized to reduce the weight thereof. Lifting equipment and accessories may be utilized to lift the form from a form holder and set same in place. Forms contain the work area as soon as it is installed to minimize fall hazards and the time, costs, and downtime associated with installation of safety measures.






FIG. 1A




FIG. 1 B




FIG.2




FIG. 3A




FIG. 3C




FIG. 3B




FIG. 3D




FIG. 3E






FIG. 3F




FIG.3G




FIG. 3H




FIG.3I




FIG. 4A




FIG.4B




FIG. 5




FIG. 6






FIG. 7




FIG. 8A




FIG.8B




FIG.8C




FIG.9A




FIG.9B




FIG.9D






FIG.9C









FIG. 10E







FIG. 10F



**FIG. 10G**



**FIG. 10H**



**FIG. 10I**




FIG. 10J




FIG. 10K







FIG. 11A





**FIG. 11D**




FIG. 11E




FIG. 11F






FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E





FIG. 13F





**STAY-IN-PLACE FORMS AND METHODS AND EQUIPMENT FOR INSTALLATION THEREOF**

**BACKGROUND OF THE INVENTION**

[0001] Embodiments of the present invention generally relate to stay-in-place fascia forms and methods and equipment for installation thereof. Conventional construction methods for building bridges are known including those which use bridge brackets, scaffolding, and many other types of form support to support the loads from wet concrete. Fascia formwork is typically made from wood or steel and requires removal after the bridge is constructed. Known apparatus and methods involve substantial issues of safety and maintenance and protection of traffic (“MPT”). Known apparatus and methods also incur substantial labor cost, material cost, and costs associated with handling and disposal of such materials.

[0002] A common method of bridge building includes the use of bridge brackets installed along the fascia of the bridge and at or near the bottom of the bridge deck. Such brackets are typically installed with wooden forms that require removal after concrete placement. This method is labor intensive and results in high material costs. Moreover, disposal costs, MPT costs (if applicable), and safety costs are incurred.

[0003] Concrete paving machines are also known for bridge construction. Such machines use truss units to carry the machine and associated parts. They also use bogie wheel, rails, and screw jack adjusters to facilitate the paving process.

**SUMMARY OF THE INVENTION**

[0004] Briefly stated, in one aspect of the present invention, a concrete form is disclosed. This concrete form includes a vertical component and a horizontal component, the vertical component located substantially perpendicular to the horizontal component. Also, the form includes an interior surface, at least a portion of the interior surface providing a form for supporting uncured concrete; wherein the uncured concrete forms a concrete structural portion upon curing of the uncured concrete; and wherein the interior surface remains attached to the concrete structural portion after formation.

**BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS**

[0005] The foregoing summary, as well as the following detailed description of preferred embodiments of the invention, will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there is shown in the drawings embodiments which are presently preferred. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown. In the drawings:

[0006] FIGS. 1A and 1B depict perspective and plan views of a stay-in-place fascia form in accordance with one embodiment of the present invention;

[0007] FIG. 2 depicts a side view of the fascia form of FIGS. 1A and 1B positioned atop the outer edge of a structural member in accordance with one embodiment of the present invention;

[0008] FIGS. 3A through 3I depict progressive side, perspective, and section views of a structure created via one process for creating a concrete structure utilizing the fascia form shown in FIGS. 1A, 1B, and 2 in accordance with one embodiment of the present invention;

[0009] FIG. 4A depicts a perspective view of a form holder in accordance with one embodiment of the present invention;

[0010] FIG. 4B depicts erection equipment for installing a plurality of forms stacked atop the form holder of FIG. 4A in accordance with one embodiment of the present invention;

[0011] FIG. 5 depicts a perspective view of a stay-in-place fascia form having a plurality of recesses in accordance with one alternate embodiment of the present invention;

[0012] FIG. 6 depicts an elevational view of a stay-in-place fascia form having a plurality of recesses in accordance with the alternate embodiment of the present invention depicted in FIG. 5;

[0013] FIG. 7 depicts a side view of a stay-in-place fascia form having a plurality of recesses in accordance with the alternate embodiment of the present invention depicted in FIGS. 5 and 6;

[0014] FIG. 8A depicts a perspective view of a stay-in-place fascia form having a plurality of apertures and a recess in accordance with one alternate embodiment of the present invention;

[0015] FIG. 8B depicts an elevational view of a stay-in-place fascia form having a plurality of apertures and a recess in accordance with the alternate embodiment of the present invention depicted in FIG. 8A;

[0016] FIG. 8C depicts a side view of a stay-in-place fascia form having a plurality of apertures and a recess in accordance with the alternate embodiment of the present invention depicted in FIGS. 8A and 8B;

[0017] FIG. 9A depicts a perspective view of a stay-in-place fascia form having a plurality of vertical recesses and a horizontal recess in accordance with one alternate embodiment of the present invention;

[0018] FIG. 9B depicts a plan view of a stay-in-place fascia form having a plurality of vertical recesses and a horizontal recess in accordance with the alternate embodiment of the present invention depicted in FIG. 9A;

[0019] FIG. 9C depicts a side view of a stay-in-place fascia form having a plurality of vertical recesses and a horizontal recess in accordance with the alternate embodiment of the present invention depicted in FIGS. 9A and 9B;

[0020] FIG. 9D depicts a cross-sectional view of the vertical recess depicted in FIGS. 9A through 9C as taken along lines 9D-9D of FIG. 9A;

[0021] FIG. 10A depicts a perspective view of a form in accordance with one embodiment of the present invention;

[0022] FIG. 10B depicts a side view of a primary support in use with the form of FIG. 10A in accordance with one embodiment of the present invention;

[0023] FIG. 10C depicts a side view of the form of FIG. 10A positioned atop the outer edge of a structural member in accordance with one embodiment of the present invention;

[0024] FIG. 10D depicts an enlarged side view of the intersection of the horizontal and vertical components of the form of FIG. 10A in accordance with one embodiment of the present invention;

[0025] FIG. 10E depicts an enlarged side view of the distal end of the horizontal component of the form of FIG. 10A in accordance with one embodiment of the present invention;

[0026] FIG. 10F depicts a side view of a secondary support for use with the form of FIG. 10A in accordance with one embodiment of the present invention;

[0027] FIG. 10G depicts a top view of a secondary support for use with the form of FIG. 10A in accordance with one embodiment of the present invention;

[0028] FIG. 10H depicts a top view of an interior reinforcement for use with the form of FIG. 10A in accordance with one embodiment of the present invention;

[0029] FIG. 10I depicts a top view of the upper plate of the primary support of FIG. 10B;

[0030] FIG. 10J depicts an enlarged side view of the distal end of the horizontal component of the form of FIG. 10A having an alternate distal end and upwardly facing surface in accordance with one embodiment of the present invention;

[0031] FIG. 10K depicts an enlarged side view of the distal end of the horizontal component of the form of FIG. 10A having an alternate distal end that includes a thickened distal end in accordance with one embodiment of the present invention;

[0032] FIG. 11A depicts a perspective view of an alternate form mounted atop a concrete structural member in accordance with one embodiment of the present invention;

[0033] FIG. 11B depicts a side view of the alternate form of FIG. 11A in accordance with one embodiment of the present invention;

[0034] FIG. 11C depicts an enlarged side view of the intersection of the horizontal and vertical components of the form of FIG. 11A in accordance with one embodiment of the present invention;

[0035] FIG. 11D depicts a plan view of the alternate form of FIG. 11A in accordance with one embodiment of the present invention;

[0036] FIG. 11E depicts a side view of the alternate form of FIG. 11A mounted atop a concrete structural member in accordance with one embodiment of the present invention;

[0037] FIG. 11F depicts a side view of a secondary support for use with the form of FIG. 11A in accordance with one embodiment of the present invention;

[0038] FIG. 12A depicts a perspective view of an alternate form atop a structural member in accordance with one embodiment of the present invention;

[0039] FIG. 12B depicts a side view of the alternate form of FIG. 12A mounted atop a structural member in accordance with one embodiment of the present invention;

[0040] FIG. 12C depicts an enlarged side view of the intersection of the horizontal and vertical components of the form of FIG. 11A in accordance with one embodiment of the present invention;

[0041] FIG. 13A depicts a perspective view of an alternate form atop a structural member in accordance with one embodiment of the present invention;

[0042] FIG. 13B depicts a side view of the alternate form of FIG. 13A mounted atop a structural member in accordance with one embodiment of the present invention; and

[0043] FIG. 13C depicts a side view of a primary support for use with forms including, but not limited to, the form of FIG. 13A in accordance with one embodiment of the present invention;

[0044] FIG. 13D depicts a side view of an alternate primary support for use with forms including, but not limited

to, the form of FIG. 13A in accordance with one embodiment of the present invention;

[0045] FIG. 13E depicts a side view of another alternate primary support for use with forms including, but not limited to, the form of FIG. 13A in accordance with one embodiment of the present invention; and

[0046] FIG. 13F depicts a side view of an alternate primary support for use with forms including, but not limited to, the form of FIG. 13A in accordance with one embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

[0047] Certain terminology may be used in the following description for convenience only and is not limiting. The words “lower” and “upper” and “top” and “bottom” designate directions in the drawings to which reference is made. The terminology includes the words above specifically mentioned, derivatives thereof and words of similar import.

[0048] Where a term is provided in the singular, the inventors also contemplate aspects of the invention described by the plural of that term. As used in this specification and in the appended claims, the singular forms “a”, “an” and “the” include plural references unless the context clearly dictates otherwise, e.g., “a form” may include a plurality of forms. Thus, for example, a reference to “a method” includes one or more methods, and/or steps of the type described herein and/or which will become apparent to those persons skilled in the art upon reading this disclosure.

[0049] Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although any methods and materials similar or equivalent to those described herein can be used in the practice or testing of the present invention, the preferred methods, constructs and materials are now described. All publications mentioned herein are incorporated herein by reference in their entirety. Where there are discrepancies in terms and definitions used in references that are incorporated by reference, the terms used in this application shall have the definitions given herein.

[0050] Referring now to FIGS. 1A and 1B, depicted is an exemplary stay-in-place fascia form **100** in accordance with one embodiment of the present invention. This exemplary form **100** is utilized as a form for supporting uncured concrete, and, after the concrete has cured, form **100** remains an integral part of the structure formed thereby. This exemplary form **100** is intended for use in the construction of new bridges, specifically, bridge barriers such as traffic barriers. Although the described use of form **100** is new bridge construction and barriers for same, the systems and methods of the present invention are not limited to use for building bridges. They may be incorporated for the construction of other structures or other uses including, without limitation, bridge repair and/or rehabilitation, parapet construction, building construction, and the like.

[0051] When used for bridge building, form **100** contains the work area as soon as it is installed as discussed in greater detail below, which minimizes or eliminates fall hazards, thereby eliminating the time, costs (e.g., labor costs, removal costs, disposal costs, etc.), and downtime associated with installation of safety measures that are typically required (e.g., formwork, scaffolding, road closure, etc.) to contain the work area. That is, minimal or zero excess

materials are needed to contain the work area since the form performs this task while also remaining in place after construction to become part of the structure being built. Also, the disruption of traffic or other environmental considerations beneath the structure being built is minimized as all work can be safely performed from atop the structure.

[0052] Now referring to FIGS. 1A, 1B, and 2, form 100 is a relatively thin, substantially L-shaped panel that includes vertical component 102 and horizontal component 104. In the depicted embodiment, vertical component 102 is located substantially perpendicular to horizontal component 104, however, alternate orientations may be substituted.

[0053] Vertical and horizontal components 102 and 104, respectively, have thicknesses  $T_1$  of approximately two inches (2"), however, alternate thicknesses may be substituted without departing from the scope of the present invention. Also, embodiments are envisioned in which the thicknesses of the vertical and horizontal components are not equal.

[0054] The height  $H_1$  of form 100 is approximately forty four inches (44"), the width  $W_1$  is approximately two feet (2'), and the length  $L_1$  is approximately sixty inches (60"), however, varied dimensions may be substituted to accommodate, for example, desired size of the structure being built as well as material strength and geometric boundaries. For example, alternate embodiments are envisioned in which width  $W_1$  is approximately twelve inches (12"), but the invention is not so limited.

[0055] As best seen in FIG. 2, in the depicted embodiment of the present invention, upwardly facing surface 222 of vertical component 102 inclines upwardly and inwardly toward interior surface 106 at an angle of approximately thirty degrees (30°), however, varying angles may be substituted.

[0056] Form 100 has an interior surface 106 that includes upwardly facing surface 108 of horizontal component 104, inwardly facing surface 110 of vertical component 102, and inwardly facing surface 234 of joining component 210. In the exemplary embodiment of the present invention shown in FIG. 2, joining component 210 extends at an angle of 45 degrees (45°) relative to said inwardly facing surface 110 of said vertical component and said upwardly facing surface 108 of said horizontal component. However, alternate configurations may be substituted without departing from the scope hereof.

[0057] Interior surface 106 provides a form for supporting uncured concrete as discussed in greater detail below. Once the concrete has cured, form 100 remains in place and forms a structural portion of the bridge being built or remains in place as a permanent part that does not have structural significance. That is, interior surface 106 remains attached to the cured concrete after curing/formation of same. In this case, exterior surface 112 becomes an exterior surface of the bridge. In some embodiments such as the one depicted in FIG. 2, exterior surface 112 includes one or more ornamental features 240 or other aesthetics to provide a decorative exterior or surface for the structure. Exterior surface 112 may include the downwardly facing surface 114 (e.g., a soffit) of horizontal component 104, the outwardly facing surface 116 of vertical component 102, bevel 212, and/or any portion or combinations of the aforementioned items.

[0058] In some embodiments of the present invention such as that shown in FIG. 2, the upper corner of a distal end of horizontal component 104 is in the form of rounded edge

214. However, alternate configurations and/or shapes for this edge may be substituted including, without limitation a squared edge, a chamfered edge or edge treatment. Or edge 214 may be omitted, without departing from the scope hereof.

[0059] Additionally, in some embodiments of the present invention such as that shown in FIG. 2, bevel 212 extends longitudinally along the intersection of outwardly facing surface 116 of vertical component 102 and downwardly facing surface 114 of horizontal component 104. Bevel 212 acts as a drip edge to cause water to drip downward rather than along downwardly facing surface 114. Bevel 212 is located at an angle of forty-five degrees (45°) relative to outwardly facing surface 116 of vertical component 102 and downwardly facing surface 114 of horizontal component 104. However, alternate configurations and/or shapes for this bevel may be substituted, or bevel 212 may be omitted, without departing from the scope hereof.

[0060] Additionally, in some embodiments of the present invention such as that shown in FIG. 2, protrusion 216 extends below downwardly facing surface 114 of horizontal component 104 directly below joining component 234. Protrusion 216 has a substantially semicircular cross-section, and it acts as a drip strip to cause water to drip downward rather than along downwardly facing surface 114. Protrusion 216 and bevel 212 both act to eliminate or minimize the amount of water that reaches structural support 302 in an effort to minimize corrosion thereof. However, alternate configurations, locations, and/or shapes for this protrusion may be substituted, or protrusion 216 may be omitted, without departing from the scope hereof including, without limitation, a longitudinal recess.

[0061] Form 100 may be formed of many different types of materials or combinations thereof, provided that the strength of the material, or combination of materials, is sufficient to hold the implied loads such as that of the uncured concrete. In the depicted embodiment, form 100 is made from 5,000 PSI fiber-reinforced concrete, however, other materials, or combinations of materials, including, but not limited to, polymers and/or high strength concretes may be substituted.

[0062] Optionally, form 100 may include an interior reinforcement 242. In the depicted embodiment, interior reinforcement 242 is a four-by-four (4"×4") epoxy-coated, welded wire mesh that extends substantially throughout the height of vertical component 102 and the width of horizontal component 104 with the exception of a bend at the intersection thereof. The portion of the depicted interior reinforcement 242 located within vertical component 102 is located approximately equidistant from inwardly facing surface 110 and outwardly facing surface 116. The portion of the depicted interior reinforcement 242 located within horizontal component 104 is located approximately equidistant from upwardly facing surface 108 and downwardly facing surface 114. These two portions are connected to each other via a curve in the interior reinforcement, such curve having a radius of approximately four inches (4"). However, alternate locations and configurations may be substituted including, without limitation, reinforcements made of carbon mesh or other materials having tensile strength and reinforcements having partially exposed portions (portions that extend beyond the confines of form 100). Or interior reinforcement 242 may be omitted without departing from the scope hereof.

[0063] Form 100 may optionally include a rabbet such as rabbet 218 to assist in placement of form 100 atop a structural member 302 (e.g., a girder, stringer, etc.) as discussed in greater detail below. In the depicted embodiment, rabbet 218 extends longitudinally along the distal lower corner of horizontal component 104 and it is substantially L-shaped. That is, when form 100 is viewed in its upright position, rabbet 218 is in the form of an L that has been inverted and rotated 90 degrees counterclockwise. However, alternate shapes may be substituted without departing from the scope hereof. Further, although structural member 302 is depicted in the shape of a traditional bridge girder, structural member may have virtually any shape or configuration and form 100 and/or rabbet 218 may be modified accordingly, as needed.

[0064] As best seen in FIG. 2, form 100 includes a plurality of inserts 202. In the depicted embodiment, inserts 202 are threaded, plastic inserts such as the precast concrete plastic inserts manufactured by A.C. Miller Concrete Products, Inc. and having model no. IN-025 through IN-150. However, alternate inserts may be substituted including, but not limited to, galvanized steel inserts and non-threaded inserts. Or, apertures passing completely through horizontal and/or vertical components 102 and 104, respectively, may be substituted. In the depicted embodiment, inserts 202 are embedded in form 100 during manufacturing thereof (e.g., during the casting of the form via a concrete mold), however, alternate embodiments are envisioned in which such inserts are installed after casting and/or placement of form 100 as discussed in greater detail below. Additionally, although form 100 includes seven (7) inserts 202, varying quantities may be substituted. For example, in one alternate embodiment, a plurality of inserts are provided in the form of a grid to allow multiple exterior reinforcement style form attachments 206 to be installed (as discussed below) to increase the coupling between form 100 and any adjacent cast-in-place concrete structures or structure portions.

[0065] In the depicted embodiment, inserts 202 are compatible with a variety of form attachments 206. Form attachments 206 may perform any one of a number of functions including, without limitation, assisting with installation of form 100, increasing the strength of the interface between form 100 and the cured concrete, and the like. Form attachments 206 may be any one of a plurality of commercially available connection devices. For example, in the depicted embodiment, form attachments 206a and 206b are one-half inch (1/2") threaded shank eye bolts with a shoulder as manufactured by Chicago Hardware, and form attachments 206c and 206d are exterior reinforcements. In the depicted embodiment, this exterior reinforcement is a reinforcement bar of Grade 60 (i.e., 60,000 PSI) such as an imperial size #4, one half inch (1/2") diameter reinforcement bar that includes threads on its proximal end (e.g., these threads may be added during manufacturing or during construction of the structure) and a J-shaped hook on its distal end. However, alternate exterior reinforcements may be substituted without departing from the scope hereof. Form attachments 206 connect to form 100 by simply threading of same into a compatible insert such as insert 202 as discussed above.

[0066] Form attachments 206a and 206b facilitate attachment of a tie or the like during installation of form 100 and prior to the pouring of concrete as discussed in greater detail below. That is, the tie may be threaded through the eye of form attachments 206a and 206b prior to the tying thereof.

In the depicted embodiment, form attachments 206a are threaded into inserts 202a, and form attachments 206b are threaded into inserts 202c as depicted in FIG. 2.

[0067] Additionally, a form attachment 206a or 206b may be threaded into insert 202d to facilitate coupling of form 100 to a lifting cable 310 via a coupler 309 or the like prior to placement of same as discussed below. That is, coupler 309 or the like may be inserted through a form attachment 206 and/or a shackle coupled thereto to lift facilitate the lifting of form 100 from a stack of forms and/or from a form holder such as form holder 404 as described below with respect to FIGS. 4A and 4B. In the depicted embodiment, such an attachment is threaded into insert 202d, which is located at the center of gravity of form 100. This location minimizes movement of the form during lifting and placement, however, alternate locations may be substituted without departing from the scope hereof. After the form is set in place and detached from lifting equipment 402, form attachment 206a may be removed from insert 202d to allow the threading of a different form attachment thereto including, without limitation, form attachments 206a, 206b, 206c, and/or 206d as discussed above.

[0068] Form attachments 206c and 206d increase the bond between form 100 and the concrete poured adjacent thereto. That is, after the concrete is poured, exterior reinforcement-style form attachments 206c and 206d are encased therein and form a stronger, more permanent bond between form 100 and the poured concrete after curing of the latter. However, alternate form attachments 206, or varying quantities thereof, may be omitted or substituted without departing from the scope hereof. For example, form attachments 206 may include alternate hardware capable of coupling to, without limitation, S-hooks, shackles, coil rod ties, coil loop inserts, turnbuckles, washers and nuts, welded studs or hooked brackets and the like, some or all of which is capable of purposes including, but not limited to, attaching to existing or proposed steel, wood, or concrete structural members and facilitating the attachment of inboard formwork.

[0069] In one aspect of the depicted embodiment, interconnection clip 204 is optionally mounted on upwardly facing surface 118 of the vertical components 102 of adjacent forms 100. In the depicted embodiment, each approximate half of clip 204 is mounted atop upwardly facing surface 118 of the vertical components of two adjacent forms 100 as best seen in the side view of FIG. 2. This coupling of two forms 100 via clip 204 allows clip 204 to: distribute the load of each form 100 to its adjacent forms 100, if any; maintain alignment of forms 100; and/or provide a mounting surface for a railing or railing system.

[0070] As best seen in FIG. 2, this exemplary interconnection clip 204 includes top wall 224, inner wall 226, and outer wall 228. Top wall 224 mirrors the configuration of upwardly facing surface 222 of vertical component 102. That is, top wall 224 inclines upwardly and inwardly toward inner wall 226 at an angle of approximately thirty degrees (30°). Inner and outer walls 226 and 228, respectively, extend downward from the longitudinal edges of top wall 224 and extend throughout the full length of clip 204. The bottom edges of inner and outer walls 226 and 228, respectively, are located at the same height, thereby causing inner wall 226 to be taller than outer wall 228 due to the angled nature of top wall 224. However, alternate configurations of

clip **204** may be substituted without departing from the scope hereof or clip **204** may be omitted entirely.

[0071] Interconnection clip **204** may optionally include railing support **220**. In the depicted embodiment, railing support **220** includes a cylindrical portion **230** suspended above top wall **224** by vertical railing support component **232**. Vertical railing support component **232** is approximately the same diameter as the railing to be threaded therethrough and has an inside diameter of approximately one and five-eighth inches (1 $\frac{5}{8}$ " ), and is located along the approximate longitudinal centerline of top wall **224**. In the depicted embodiment, clip **204** only extends approximately one-tenth the length of form **100**, however, other distances may be substituted including, without limitation, a distance equal to the full length of form **100**. Cylindrical portion **230** sits atop vertical railing support component **232** and is approximately centered thereupon. It extends the full length of top wall **222**. However, alternate configurations and/or locations may be substituted without departing from the scope hereof.

[0072] After installation of form **100**, a railing (e.g., a cable, pipe, etc.) may be installed through railing support **220** to extend partially or throughout the length of the bridge or other structure in accordance with OSHA guidelines (to prevent or minimize falls during construction of the structure) or for other purposes. That is, in one embodiment of the present invention, the height of form **100** is sufficient to eliminate the need for a railing as per OSHA requirements. However, once the deck **318** is poured, the height between the top of form **100** and deck **318** may become less than the minimum required by OSHA. In such a scenario, a railing may be added to meet OSHA requirements. However, alternate configurations of railing support **220** may be substituted without departing from the scope hereof or support **220** may be omitted entirely. Railing support **220** may also be eliminated without departing from the scope hereof. In one such embodiment, the height of form **100** is increased to allow the panel to exceed the railing height required by OSHA, thereby eliminating the need for a railing.

[0073] Referring now to FIGS. 3A through 3I, depicted are progressive side, perspective, and section views of a structure created via one process for installing form **100** on a structural member **302** in accordance with one embodiment of the present invention. In the depicted example, structural member **302** is a bridge fascia girder installed as known in the art. Prior to placement of form **100** on structural member **302**, structural member attachment **304** is—mounted on the structural member via welding, J-hook bracket, or the like to facilitate the installation of ties that hold form **100** in place prior to the pouring of the concrete deck. In the depicted embodiment, structural member attachment **304** is a welded stud such as a High Strength, CPL Stud as manufactured by Nelson Stud Welding and having part no. 101021688.

[0074] In the depicted exemplary form **100**, structural member attachment **304** is mounted approximately one and one half inches (1 $\frac{1}{2}$ " ) from the inner edge of upwardly facing surface **306** of structural member **302**, however, alternate locations may be substituted. Structural member attachments **304** are located such that approximately two (2) structural member attachments **304** are utilized for installation of each form **100** as best seen in FIG. 3B, however, varying quantities may be substituted.

[0075] Also, alternate structural member attachments may be substituted without departing from the scope hereof. For

example, structural member attachments may be type B4L standoff support studs, type R9L rope hook studs, Type R6P rectangular slotted studs, type SBL shoulder studs, type TBL internally threaded studs, all as manufactured by Nelson Stud Welding. Or, alternatively, structural member attachments may be designed to hook onto the side of structural member **302**, thereby eliminating the need for welding thereof. One such structural member attachment is the Century Series Hanger having model no. C130 as manufactured by Dayton Superior.

[0076] In yet another alternate embodiment, a formwork attachment may be substituted for, or used in addition to, the structural member attachment. One such formwork attachment is a galvanized hook that hooks into a slot that is cut into formwork such as formwork **312**. Other formwork attachments may include, but are not limited to, Hook Bolts having model no. D1-J, D1LA, or D1L, coil loop straight inserts having model no. B16, Inside Tie Rods having model nos. D1 and D18, and/or a heavy duty screed support having model no. G15, all as manufactured by Dayton Superior.

[0077] After structural member attachments **304** are in place (as best seen in FIG. 3C), form **100** may be lifted via any capable lifting equipment (e.g., a crane, davit, etc.) such as that equipped with a lifting cable **310** or the like for placement atop structural member **302**. One such method is described below with respect to FIG. 4B. Lifting cable **310** and an associated coupler **309** or the like may attach to form **100** via a direct or indirect attachment to form attachment **206a**. For example, intermediate coupling devices such as a shackle or the like may couple coupler **309** to form attachment **206a**.

[0078] FIG. 3A depicts a side view of form **100** after it is lowered atop structural member **302** such that rabbet **218** aligns with the upper and outer edge of structural member **302**. For the purposes of FIG. 3A, **202a** located to the right of **202d** (as best seen in FIG. 1B) has been removed to show one method of connecting lifting equipment **402** to insert **202d**. Form **100** is then rotated by lifting equipment **402** until vertical component **102** is substantially plumb (i.e., substantially perpendicular to upwardly facing surface **306** of structural member **302**) as best seen in the side view of FIG. 3C.

[0079] Thereafter, form **100** is tied in place utilizing form attachments **206a**, **206b**, structural member attachments **304**, and one or more tie(s) **314** as described below in order to secure form **100** to structural member **302**. FIG. 3B depicts form **100** after it has been tied in place. It should be noted that, in the depicted embodiment, tie(s) **314b** are the primary support element (i.e., the primary mechanism utilized to hold the form in place prior to the pouring of the concrete) and tie(s) **314a** are safety elements that prevent or minimize form **100** from being accidentally dislodged from structural support **302**. Moreover, tie(s) **314a** are installed in a substantially horizontal member as compared to tie(s) **314b**, which are installed at an angle. End fittings for each of these ties may also be selected as needed. For example, tie(s) **314a** may include adjusting nuts on one or more ends, whereas tie(s) **314b** may include one or more turnbuckle-style end fittings. However, any end fitting may be substituted, or omitted, without departing from the scope of the present invention.

[0080] Tie(s) **314** may be Inside Tie Rods as manufactured by Dayton Superior and having model no. D1 or D18. Tie rods may include various end fittings on one or both ends

including, without limitation, turn buckle fittings. However, no such fittings are required to implement the present invention. Also, alternate structural member attachments and/or ties including, without limitation, Richmond tie rod units may be substituted without departing from the scope hereof.

[0081] Form 100 may be disconnected from lifting equipment 402 as soon as it is secured in place, and any form attachments required for connection of form 100 to lifting equipment 402 may be removed, reused, or left in place/unused. Any other desired form attachments including, without limitation, exterior reinforcements or the like may be installed. For example, form attachments 206c and/or 206d may be installed in inserts 202b and/or 202d to further increase the bond between the cured concrete and form 100 as described in greater detail above. FIG. 3C depicts such exterior reinforcements after installation. Then, railing 316 may be threaded through railing supports 220. FIGS. 3D, 3E, and 3G depict railing 316 after installation. It should be noted that form attachment(s) such as form attachments 206c and 206d may be installed at an alternate point in the process so long as they are installed prior to the pouring of deck 318. Also, railing 316 may be installed at any point in the installation process.

[0082] FIG. 3B depicts a perspective view of form 100 mounted and tied atop structural member 302. FIGS. 3B and 3C also depict deck formwork 312, which is installed on the opposing side of structural member 302 utilizing methods known in the art. Although it is anticipated that formwork 312 is installed prior to placement of form 100 atop structural member 302, embodiments of the present invention are also envisioned in which form 100 is installed prior to formwork 312. It should also be noted that although formwork 312 is shown as an unfilled stay in place form, filled stay in place forms are also compatible with the systems and methods of the present invention. Such forms may be filled with fillers that include, but are not limited to, foam and concrete.

[0083] After form 100 is tied in place, it contains the work area as soon as it is installed as discussed in greater detail below, which minimizes or eliminates fall hazards, thereby eliminating the time, costs (e.g., labor costs, removal costs, disposal costs, etc.), and downtime associated with installation of safety measures that are typically required (e.g., formwork, scaffolding, road closure, etc.) to contain the work area. That is, minimal or zero excess materials are needed to contain the work area since the form performs this task while also remaining in place after construction to become part of the structure being built. Also, the disruption of traffic or other environmental considerations beneath the structure being built is minimized as all work can be safely performed from atop the structure.

[0084] FIG. 3D depicts a perspective view of form 100 mounted and tied atop structural member 302 as well as deck formwork 312, deck rebar 320, and primary barrier rebar 322 after it is installed on the opposing side of structural member 302, structural member 302, and upwardly facing surface 108 of horizontal component 104. Deck rebar 320 and primary barrier rebar 322 are installed as is also known in the art.

[0085] Referring now to FIG. 3E, depicted is a perspective view of form 100, structural member 302, and formwork 312 after the concrete has been poured to form deck 318. Deck 318 is formed upon the curing of the concrete.

[0086] After the concrete is poured and cured, the portion of ties 314b extending above deck 318 may optionally be removed from form attachments 206a as depicted in the side view of FIG. 3F. However, form attachments 206b and 206c remain after curing of the concrete as they are encased therein.

[0087] The encasing of exterior reinforcement style form attachments 206c in the concrete deck 318 (and form attachment 206d in barrier 326) further couples form 100 to concrete deck 318 and barrier 326, and facilitates the ability of form 100 to accommodate the shear and moment forces placed thereupon by the weight of the concrete deck 318. As discussed above, the portion of tie(s) 314b that extend above upwardly facing surface 324 of concrete deck 318 may optionally be removed after curing of the deck concrete. Alternatively, it may be left in place and encased in barrier 326 (See FIG. 3I). If a portion of tie(s) 314b are removed, form attachments 206a may also optionally be removed and/or replaced with new form attachments including, but not limited to, exterior reinforcement style form attachments such as form attachments 206c and 206d to increase the coupling of form 100 to the barrier to be mounted adjacent thereto as discussed below. Or, as is shown in the depicted embodiment, form attachments 206a are left in place and utilized to install substantially horizontal tie(s) 314c (as best seen in FIG. 3H). Ties 314(c) couple form 100 to inboard formwork 334 (i.e., the formwork utilized to pour barrier 326) prior to the pouring of the concrete for barrier 326 in an effort to further support the formwork and create a greater bond between form 100 and barrier 326 after curing of same. Tie(s) 314c also assist with resisting the pressure applied to formwork 334 and form 100 by the wet concrete poured to form barrier 326. Also, form attachments 206a may also be replaced with a differing attachment capable of coupling ties 314c to form 100 without departing from the scope hereof.

[0088] FIG. 3F depicts a side view of form 100, structural member 302, exterior reinforcement 206c, and formwork 312 after the concrete has been poured to form deck 318 including dashed lines to indicate the components encased therein, namely, deck rebar 320, primary barrier rebar 322, lower form attachment 206b, girder attachment 304, tie(s) 314a, a portion of tie(s) 314b, and exterior reinforcement 206c. As illustrated, primary barrier rebar 322 extends above upwardly facing surface 324 thereof.

[0089] FIG. 3G depicts a perspective view of deck 318 after curing of the concrete including structural member 302, formwork 312, primary barrier rebar 322, form 100, exterior reinforcement 206d, and secondary barrier rebar 328. Secondary barrier rebar 328 is installed within and above primary barrier rebar 322 as illustrated in FIG. 3G and as is known in the art.

[0090] Finally, inboard barrier formwork 334 is put in place, ties 314c are installed to secure formwork 334 to form 100, and the railing system installed for safety purposes (i.e. clips 204 and railing 316) is removed in preparation for the pouring of the barrier concrete. The railing system may be removed before or after installation of the inboard barrier formwork 334. Ties 314c are coupled to formwork attachment 336, which may be identical to, or similar to, form attachment 206a, however, such attachment 336 is coupled to formwork 334 either prior to, or after, such formwork is set in place. Then, the concrete for barrier 326 is cast in place.

[0091] FIGS. 3H and 3I depict side and perspective views of form 100, structural member 302, tie(s) 314c, deck 318, barrier 326, and formwork 312 after the concrete has been poured to form barrier 326. FIG. 3H also depicts the components encased therein, namely, deck rebar 320, primary barrier rebar 322, secondary barrier rebar 328, lower form attachment 206b, structural member attachment 304, tie(s) 314a, a portion of tie(s) 314b, tie(s) 314c and exterior reinforcements 206c and 206d. The pouring of barrier 326 above upwardly facing surface 222 forms construction joint 330 between upwardly facing surface 222 and barrier 326.

[0092] Now referring to FIG. 4, embodiments of the present invention also generally relate to apparatus, systems, and methods for storing, transporting and/or installing fascia forms.

[0093] Although the described use of such apparatus, systems, and methods is new bridge construction, the use thereof is not limited thereto.

[0094] As depicted in FIG. 4, system 400 includes, inter alia, lifting equipment 402, form holder 404, and work bridge 406. System 400 facilitates the erection/installation of a form such as, but not limited to, form 100 as discussed above. Form holder 404 is designed to support a plurality of forms in a stacked manner during storage, transportation, and installation. In the depicted embodiment, frame holder 404 is made of steel but alternate materials may be substituted including, without limitation, aluminum, other alloys, and combinations of the foregoing materials. Materials may be selected in order to minimize weight, but this is not required to implement the systems and methods of the present invention.

[0095] As best seen in FIG. 4A, form holder 404 includes base section 408, rear section 410, front section 412, rear intermediate section 414, and front intermediate section 416, all of which are substantially rectangular. In the depicted embodiment, base section 408 and all of the aforementioned sections have lengths approximately equivalent to the forms to be supported by the form holder. However, varying lengths may be substituted without departing from the scope hereof.

[0096] More specifically, form holder 404 includes a substantially rectangular, substantially horizontal base section 408. A substantially rectangular rear section 410 extends vertically from a first longitudinal side 418 of base 408, and a substantially rectangular front section 412 extends vertically from a second longitudinal side 420 of base 408. A substantially rectangular front intermediate section 416 extends at an angle of approximately forty five degrees from a first upper longitudinal end 422 of said front section to base 408, and a substantially rectangular rear intermediate section 414 extends at an angle of approximately forty five degrees from a second upper longitudinal end 424 of said rear section to base 408. Rear intermediate section 414 intersects front intermediate section 416 at an angle of approximately ninety degrees.

[0097] Additionally, in the depicted embodiment, rear intermediate section 414 has a height approximately equal to a height of form 402 minus the width of rear section 410. The height of front intermediate section 416 is then selected to be the height that allows front intermediate section 416 to be located substantially perpendicular to rear intermediate section 414 without extending beyond front section 412. Similarly, the height of front section 412 is selected to be equivalent to topmost edge 426 of front intermediate section

416. However, varying dimensions may be substituted without departing from the scope hereof.

[0098] In the depicted embodiment of the present invention, each of the base section 408, rear section 410, front section 412, rear intermediate section 414, and front intermediate section 416 are substantially rectangular and are not solid. Rather, these sections are comprised of a plurality of subframe support members 430 arranged to form substantially rectangular and/or square subframes 432 for each section. Many of these subframes 432 include angled support members 434 as depicted in FIG. 4A. Such support members are provided to increase the strength of the corresponding section.

[0099] As also shown in FIG. 4A, a plurality of vertical section supports 436 may be added to support rear intermediate section 414 and/or front intermediate section 416 as necessary to increase the load bearing capabilities of form holder 404.

[0100] The above described configuration of form holder 404 allows a plurality of forms such as forms 100 to be stacked atop form holder 404 via lifting equipment such as lifting equipment 402 as described herein. In the depicted embodiment, spacers 428 are placed at predetermined intervals between form holder 404 and the bottommost form, and also between individual forms. In the depicted embodiment, spacers 428 are furring strips having a width of approximately one inch (1"), however, alternate spacers may be substituted without departing from the scope hereof. Form holder 404 may also be used as a shipping pallet during transportation/shipping of one or more forms.

[0101] Also, embodiments of the present invention are envisioned in which one or more layers of one or more sheets of plywood is placed atop the upwardly facing surface 440 of rear intermediate section 414 and/or front intermediate section 416 to cover all or at least a portion thereof. Form 100 may be placed directly atop the plywood, or spacers 428 may be incorporated between the plywood and form 100 without departing from the scope hereof.

[0102] Forms 100 are stacked in a position in which they are rotated backwards at an angle of approximately forty five degrees. Form holder 404 of the depicted embodiment is capable of supporting approximately nine thousand (9,000) pounds, however, alternate load capabilities may be substituted without departing from the scope hereof.

[0103] As shown in FIG. 4, in the depicted embodiment, forms 100 and form holder 404 may be supported by workbridge 404 prior to installation. For example, workbridge 404 may be a Terex Bidwell thirty foot (30') by thirty four (34') foot heavy duty work bridge installed as in known in the art. The workbridge is lightweight and works within the spacing of the screed rails that are typically installed by the contractor that screeds the finished concrete. Forms and/or form holders with stacked forms may be located on one or both ends of workbridge 404 while still allowing a sufficient span between structural members to facilitate installation of forms as described herein. However, other workbridges or equipment performing a similar function may be substituted without departing from the scope hereof. The depicted embodiment of the present invention envisions a manually powered workbridge, however, workbridges having varying types of control may be substituted including, without limitation, hydraulic, motor-driven, and mechanically driven lifting equipment. In scenarios in which a hydraulic drive is used on the workbridge, the same

operating engineer might control both the hydraulic drive system and hydraulically controlled lifting equipment.

[0104] In the depicted embodiment, lifting equipment **402** is a crane. For example, lifting equipment may be a manually controlled davit crane as manufactured by Dayton and having model no. 7CZ12. However, lifting equipment having varying types of control may be substituted including, without limitation, hydraulic, motor-driven, and mechanically driven lifting equipment. In scenarios in which a hydraulic drive is used on the workbridge, the same operating engineer might control both the hydraulic drive system and the hydraulically controlled davit.

[0105] Lifting equipment **402** may rest directly atop, for example, the screed or other equipment used for leveling the concrete. This equipment including, without limitation, wheels and rails is installed as is known in the art for the purpose of leveling the concrete. In some embodiments of the present invention, a support **432** such as a beam or the like may be utilized to further support and/or raise the height of lifting equipment **402**.

[0106] In the depicted embodiment, lifting equipment **402** is equipped with a cable **310** and associated coupler **309** or the like capable of lifting individual forms via a form attachment **206a** and a coupler **309** located at the approximate center of gravity of form **100**. One such form attachment is a one-half inch ( $\frac{1}{2}$ " ) threaded shank eye bolt with a shoulder as manufactured by Chicago Hardware. Coupler **309** is passed through form attachment **206a**. A shackle or the like may also be utilized to more securely attach coupler **309** to form attachment **206a**. Thereafter, form **100** may be lifted from the stack of forms and/or form holder **404** and suspended over the side of the bridge relative to structural member **302** as shown in FIGS. 3A and 3B as discussed above. Form **100** may then be secured to structural member **302** via ties **314** and form attachments **206a** as also discussed in greater detail above with respect to FIGS. 3A through 3I.

[0107] The erection equipment allows quick installation. Further, safety is facilitated by making a positive connection with the form before it is lifted and after it is secured to the existing structure or structure being built. Moreover, the equipment allows a tie off point to facilitate safety before form **100** is installed and/or during conventional construction of the interior bridge deck bay when such construction follows the installation of form **100**. However, the forms of the present invention may be installed utilizing other methods than that described herein without departing from the scope of the present invention.

[0108] Turning now to FIGS. 5 through 7, depicted are perspective, plan, and side views of stay-in-place fascia form **700** having a plurality of recesses **703** in accordance with one alternate embodiment of the present invention. Recesses **703** decrease the weight of form **700**. Although four (4) recesses **703** are illustrated, varying quantities may be substituted without departing from the scope hereof.

[0109] In the depicted embodiment, the features of form **700** including, without limitation, inserts **702**, interior surface **706**, bevel **712**, protrusion **716**, and rabbet **718** are substantially identical to the equivalent components of form **100**, namely, inserts **202**, interior surface **106**, bevel **212**, protrusion **216**, and rabbet **218** as discussed above. That is, the only substantial difference between form **100** and form **700** is that the latter includes recesses **703** and the dimen-

sions thereof have been altered to accommodate recesses **703** while maintaining the structural integrity of form **700**.

[0110] More specifically, height  $H_7$  of form **700** is approximately forty one inches (41"), width  $W_7$  is approximately thirty seven and one half inches ( $37\frac{1}{2}$ " ), and length  $L_1$  is approximately sixty inches (60"), however, varied dimensions may be substituted to accommodate, for example, desired size of the structure being built, material strength and geometric boundaries, and/or varying recess sizes and/or quantities.

[0111] Form **700** has a thickness  $T_7$  of approximately three inches (3"); however, alternate thicknesses may be substituted without departing from the scope of the present invention.

[0112] As best seen in the plan view of FIG. 6, recesses **703** have a recess outer width RO of approximately ten inches (10") and a recess inner width RI of approximately eight inches (8"). That is, the interior surfaces surrounding the perimeter of recesses **703** slope inward at an Angle A2 of approximately 45 degrees as such surfaces extend from interior surface **706** of form **700** to interior surface **705** of recess **703**. Such angle is best seen in the side view of FIG. 7. Also, the outer latitudinal edges **707** of recesses **703** are located at a distance  $D_{7B}$  of approximately four inches from the latitudinal edges of interior surface **706**. Similarly, the outer longitudinal edges **709** of the two outermost recesses **703** are located at a distance  $D_{7A}$  of approximately four inches from the longitudinal edges of interior surface **706**. Recesses **703** have a depth RD of approximately one inch (1"). All of the aforementioned dimensions and angles illustrate one embodiment of the present invention, however, varying dimensions and/or angles may be substituted without departing from the scope hereof.

[0113] Referring next to FIGS. 8A through 8C, depicted are perspective, plan, and side views of stay-in-place fascia form **800** having a pair of apertures **803** and a recess **813** in accordance with one alternate embodiment of the present invention. Apertures **803** allow the form to be secured in place by a coupler such as a rod or the like. That is, a first end of the coupler is coupled to the structural member on which form **800** sits via any one of a plurality of methods known in the art. The second end of the coupler passes through a respective aperture **803**. Thereafter, fasteners (e.g., nuts and bolts) may be fastened to the second end of the coupler to prevent or minimize the possibility of the coupler disengaging itself from aperture **803**. Although two (2) apertures **803** are illustrated, varying quantities may be substituted without departing from the scope hereof.

[0114] Recesses **813** decrease the weight of form **800**. Although one (1) substantially rectangular, bi-level recess **813** is illustrated, varying quantities and/or shapes may be substituted without departing from the scope hereof.

[0115] In the depicted embodiment, the features of form **800** including, without limitation, insert **802d**, interior surface **806**, bevel **812**, protrusion **816**, and rabbet **818** are substantially identical to the equivalent components of form **100**, namely, insert **202d**, interior surface **106**, bevel **212**, protrusion **216**, and rabbet **218** as discussed above. That is, the only substantial difference between form **100** and form **800** is that the latter includes recess **813**, apertures **803** in lieu of inserts **202**, and the dimensions thereof have been altered.

[0116] More specifically, the height  $H_8$  of form **800** is approximately forty one and  $\frac{5}{16}$  inches ( $41\frac{5}{16}$ " ), the width



$W_8$  is approximately thirteen and  $\frac{3}{16}$  inches ( $13\frac{3}{16}$ " ), and the length  $L_8$  is approximately sixty inches (60"), however, varied dimensions may be substituted to accommodate, for example, desired size of the structure being built, material strength and geometric boundaries, and/or varying aperture sizes and/or quantities.

[0117] Form **800** has a thickness  $T_8$  of approximately two inches (2"); however, alternate thicknesses may be substituted without departing from the scope of the present invention.

[0118] As best seen in the plan view of FIG. 8B, recess **813** have a recess width  $RW_8$  of approximately fifty four inches (54"). The longitudinal edges **809** of recess **813** are located approximately three inches (3") from the longitudinal edges of interior surface **806**. Recess **813** has an overall recess height  $RH_8$  of approximately thirty nine and  $\frac{3}{16}$  inches ( $39\frac{3}{16}$ " ). Recess **813** includes upper and lower rectangular sections **821** and **823**, respectively, having recess depths  $RD_{8A}$  and  $RD_{8B}$  of approximately one inch (1") and one-half inch ( $\frac{1}{2}$ " ), respectively. The width  $RW_8$  of upper and lower rectangular sections **821** and **823**, respectively, are both approximately fifty four inches (54"). The recess heights  $RH_{8A}$  and  $RH_{8B}$  are approximately ten and  $\frac{3}{16}$  inches ( $10\frac{3}{16}$ " ) and twenty nine and one eighth inches ( $29\frac{1}{8}$ " ), respectively. All of the aforementioned dimensions and angles illustrate one embodiment of the present invention, however, varying dimensions and/or angles may be substituted without departing from the scope hereof.

[0119] In the depicted embodiment, the center point of each aperture **803** is located at a height  $AH_8$  of approximately two feet (2') as best seen in FIG. 8C. Additionally, the center points of the two apertures **803** are located at a distance  $AD_1$  of approximately thirty inches (30") from each other and at a distance  $AD_2$  of approximately fifteen inches (15") from the longitudinal edge of interior surface **806** and a distance  $AD_3$  of approximately twelve inches from longitudinal edge **809** of recess **813** as depicted in FIG. 8B. However, varying locations and/or quantities of aperture **803** may be substituted without departing from the scope hereof.

[0120] As best seen in FIG. 8C, apertures **803** have a frusto-conical shape, however, varying shapes may be substituted without departing from the scope hereof.

[0121] Turning now to FIGS. 9A through 9C, depicted are perspective, plan, side, and cross-sectional views of stay-in-place fascia form **900** having a plurality of vertical recesses **903** and a horizontal recess **913** in accordance with one alternate embodiment of the present invention. Recesses **903** and **913** decrease the weight of form **900**. Although nineteen (19) vertical recesses **903** and one (1) horizontal recess **913** are illustrated, varying quantities may be substituted without departing from the scope hereof.

[0122] In the depicted embodiment, the features of form **900** including, without limitation, inserts **902**, horizontal component **904**, interior surface **906**, bevel **912**, protrusion **916**, and rabbet **918** are substantially identical to the equivalent components of form **100**, namely, inserts **202**, horizontal component **104**, interior surface **106**, bevel **212**, protrusion **216**, and rabbet **218** as discussed above. That is, the only substantial difference between form **100** and form **900** is that the latter includes vertical recesses **903**, horizontal recess **913**, and the dimensions thereof have been altered to accommodate recesses **903** and **913** while maintaining the structural integrity of form **900**.

[0123] More specifically, height  $H_9$  of form **900** is approximately forty one inches and five sixteenths inches ( $41\frac{5}{16}$ " ), width  $W_9$  is approximately twenty five inches (25"), and length  $L_9$  is approximately sixty inches (60"), however, varied dimensions may be substituted to accommodate, for example, desired size of the structure being built, material strength and geometric boundaries, and/or varying recess sizes and/or quantities.

[0124] Form **900** has a thickness  $T_9$  of approximately two inches (2"); however, alternate thicknesses may be substituted without departing from the scope of the present invention.

[0125] As best seen in the plan view of FIG. 9B, vertical recesses **903** have a recess width  $RW_{9V}$  of approximately three quarters of an inch ( $\frac{3}{4}$ " ) and a semicircular cross section, the latter of which is best seen in the cross-sectional view of FIG. 9D. The longitudinal centerlines of each vertical recess **903** are located equidistantly at a distance  $D_{9A}$  of approximately three inches (3") from all other recess longitudinal centerlines and the longitudinal edges of interior surface **906**. Also, the outer latitudinal edges **907** of vertical recesses **903** are located at a distance  $D_{9B}$  of approximately four inches from the latitudinal edges of interior surface **906**. Similarly, as also stated above, the outer longitudinal edges **909** of the two outermost recesses **903** are located at a distance  $D_{9A}$  of approximately four inches from the longitudinal edges of interior surface **906**. Recesses **703** have a depth  $RD_{9V}$  of approximately three eighths of an inch ( $\frac{3}{8}$ " ) and a height  $RH_{9V}$  of approximately twenty five and one-sixteenth inches ( $25\frac{1}{16}$ " ). All of the aforementioned dimensions and angles illustrate one embodiment of the present invention, however, varying dimensions and/or angles may be substituted without departing from the scope hereof.

[0126] As best seen in the perspective and side views of FIGS. 9A and 9C, recess **913** is located in horizontal component **904** and has a length approximately equivalent to the length  $L_9$  of form **900**. The width of recess **913** extends from the distal longitudinal edge **907** of horizontal component **904** inward at a width  $RW_{9H1}$  of approximately fourteen and one quarter inches ( $14\frac{1}{4}$ " ). Recess side surface **915** is angled downward as it extends outward at an angle of approximately 45 degrees ( $45^\circ$ ), thereby decreasing the width of recess **913** to a width  $RW_{9H2}$  of approximately thirteen and three quarters inches ( $13\frac{3}{4}$ " ) on its bottommost surface. The recess height  $RH_{9H}$  is one half inch ( $\frac{1}{2}$ " ). All of the aforementioned dimensions and angles illustrate one embodiment of the present invention, however, varying dimensions and/or angles may be substituted without departing from the scope hereof.

[0127] Turning next to FIGS. 10A through 10G, depicted is an exemplary alternate stay-in-place form **1000** in accordance with one alternate embodiment of the present invention. Form **1000** is mounted parallel to, and tied atop, a structural member **302**, as discussed hereinabove. This exemplary form **1000** is utilized as a form for supporting uncured concrete, and, after the concrete has cured, form **1000** remains an integral part of the structure formed thereby. This exemplary form **1000** is intended for uses similar to the uses of form **100**, and provides similar benefits to form **100**, as described in greater detail above.

[0128] Similar to form **100**, form **1000** is a relatively thin, substantially L-shaped panel that includes vertical component **1002** and horizontal component **1004**. In the depicted

embodiment, vertical component **1002** is located substantially perpendicular to horizontal component **1004**, however, alternate orientations may be substituted.

[0129] Vertical component **1002** and the proximal portion of horizontal component **1004** have thicknesses  $T_1$  of approximately three inches (3"). The thickness  $T_2$  of the distal end of horizontal component is thicker (i.e., three and seven thirty seconds ( $3\frac{7}{32}$ ) inches), however, alternate thicknesses may be substituted without departing from the scope of the present invention. That is, in the depicted embodiment, the thickness of horizontal component **1004** gradually increases starting at its intersection with joining component inwardly facing surface **1234**, however, alternate sizing and configurations may be substituted without departing from the scope hereof.

[0130] The height  $H_{1000}$  of form **1000** is approximately forty inches (40"), the width  $W_{1000}$  is approximately fifteen and thirty-five hundredths inches (15.35"), and the length  $L_{1000}$  is approximately sixty inches (60"), however, varied dimensions may be substituted to accommodate, for example, desired size of the structure being built as well as material strength and geometric boundaries.

[0131] In the depicted embodiment, the features of form **1000** including, without limitation, insert **1202d**, vertical component interior surface **1006**, bevel **1212**, vertical component upwardly facing surface **1222**, horizontal component upwardly facing surface **1008**, vertical component inwardly facing surface **1110**, joining component inwardly facing surface **1234**, joining component **1210**, ornamental features **1240**, horizontal component downwardly facing surface **1114**, and protrusion **1216** are substantially identical to the equivalent components of form **100**, namely, insert **202d**, interior surface **106**, bevel **212**, upwardly facing surface **222**, upwardly facing surface **108**, inwardly facing surface **110**, inwardly facing surface **234**, joining component **210**, ornamental features **240**, downwardly facing surface **114**, and protrusion **216** as discussed above with the following exceptions.

[0132] Rabbet **1218** is substantially identical to rabbet **218** of form **100** with the exception of top and side surfaces **1050** and **1052**, respectively. More specifically, in the embodiment of the present invention depicted in FIGS. **10A** through **10K**, as best seen in FIG. **10E**, the rabbet **1218** includes a rabbet **1218** defined by top and side surfaces **1050** and **1052**, respectively. Side surface **1052** tapers inwardly as it extends downwardly at an angle of approximately fifteen and one half (15.5) degrees beyond vertical, and top surface **1050** tapers upwardly as it extends distally away from side surface **1052** at an angle of approximately fifteen and one half (15.5) degrees above horizontal. Consequently, the top and side surfaces **1050** and **1052** are located at an angle of greater than ninety degrees relative to each other. Also, each of top and side surfaces **1050** and **1052**, respectively, are located at an angle of greater than ninety degrees relative to the vertical and horizontal planes **1059** and **1057**, respectively, of the innermost point **1055** of the rabbet **1218**. That is, top surface **1050** is greater than ninety degrees relative to the vertical plane **1059** of point **1055**, and side **1052** is greater than ninety degrees relative to the horizontal plane **1057** of innermost point **1055**. However, alternate angles and/or configurations for the sides of rabbet **1218** may be substituted without departing from the scope hereof. Rabbet **1218**

may also have varying cross-sections without departing from the scope hereof, including, without limitation, a square cross-section.

[0133] Also, in the depicted embodiment of the present invention, the upper corner of a distal end of horizontal component **1004** is in the form of chamfered edge **1214** rather than the rounded edge **214** shown for form **100**. Further, chamfered edge **1214** is chamfered at an angle of approximately forty-five degrees relative to horizontal component upwardly facing surface **1008** and horizontal component distal vertical surface **1054**, however, alternate angles may be substituted without departing from the scope hereof. However, alternate configurations and/or shapes for this edge may be substituted including, without limitation a squared edge, a rounded edge or edge treatment.

[0134] Additionally, form **1000** includes internal reinforcement **1056** as depicted in FIG. **10H** and similar to internal reinforcement **242** of form **100**. In the depicted embodiment, internal support **1056** is a four (4) inch by four (4) inch grid of welded wire mesh W4.0 by W4.0 Grade 60 Galvanized Steel ASTM Designation A 185 A 641, located internal to form **1000** as depicted in dashed lines in FIGS. **10A** and **10C** through **10E**. As seen in FIG. **10E**, internal reinforcement **1056** is substantially horizontal internal to horizontal component **1004** until a point slightly distal to insert **1202c**, at which point it angles upwardly as it approaches the distal end of substantially horizontal component **1004** at an angle that retains internal reinforcement **1056** at the vertical midpoint of horizontal component **1004**. However, alternate angles, internal reinforcements and/or internal reinforcement configurations may be substituted without departing from the scope hereof. Or, internal reinforcement may be omitted partially or entirely without departing from the scope hereof.

[0135] Further, in form **1000**, similar to form **100**, the inserts **1202** of the substantially horizontal component **1004** and the substantially vertical component **1002** facilitate attachment of form **1000** to an existing structural member **302**. However, the attachment mechanism **1060** utilized in conjunction with such form attachments differ.

[0136] More specifically, in the depicted embodiment, attachment mechanism **1060** includes, primary support **1253**, secondary support **1254**, primary tie system **1298**, and secondary tie system **1252**. In the depicted embodiment, primary tie system **1298** includes, rod **1249**, rod insert **1250a**, adjustable fastener **1251**, and form attachment **1206a** which are coupled to form **1000** and the top of structural member **302** diagonally at an angle of approximately forty-five (45) degrees, however alternate angles may be substituted without departing from the scope hereof.

[0137] In the depicted embodiment, the primary tie system **1298** includes at least one coil rod **1249** such as an inline, Dayton Superior B12 coil rod made of a rigid material such as steel etc. having a one-half ( $\frac{1}{2}$ ) inch diameter capable of withstanding a load of at least 18,000 pounds. One end of rod **1249** is connected to rod insert **1250b** of primary support **1253** and the other end of rod **1249** is connected to rod insert **1250a**. The rod inserts **1250a** and **1250b** are constructed of a rigid material such as steel and the like and have a diameter of one half ( $\frac{1}{2}$ ) inch and length of six (6) inches. In the depicted embodiment, these rod inserts are Dayton Superior one half inch ( $\frac{1}{2}$ " diameter by six inch (6") length B16 coil loop inserts.

[0138] Rod insert **1250a** is connected to form **1000** by means of an adjustable fastener **1251** and form attachment **1206a**. In the depicted embodiment, adjustable fastener **1251** is a turnbuckle with jaw ends made of a rigid material such as steel etc. and having a three quarter ( $\frac{3}{4}$ ) inch diameter, and form attachment **1206a** is in the form of a one half ( $\frac{1}{2}$ ) inch diameter shoulder eyebolt (also made of a rigid metal such as steel etc.) affixed to form **1000** by insertion into insert **1202d**. Adjustable fastener **1251** allows the spacing connection between form attachment **1206a** and rod **1249** to be fine-tuned by spinning it in either direction to engage the threads, which may be used, for example, to bring the form into a plumb position. This may be done via a wrench or the like.

[0139] Rod insert **1250b** is integral to primary support **1253** as shown in FIG. 10B. In the depicted embodiment, primary support **1253** includes two substantially rectangular bent plates, namely, upper and lower plates **1246** and **1245**, respectively. The downwardly facing surface **1280** of the proximal end of upper plate **1246** is welded to the upwardly facing surface **1282** of the proximal end of lower plate **1245**. However, alternate embodiments are envisioned in which the welding is eliminated and two separate plates are utilized and are held together via a fastener such as fastener **1251**.

[0140] Upper and lower plates **1246** and **1245**, respectively, have substantially rectangular shapes and are made of a rigid metal such as, but not limited to, steel. In the depicted embodiment, upper bent plate **1246** is four (4) inches wide, ten (10) inches long, and one half ( $\frac{1}{2}$ ) inch thick, and it is bent at an angle of approximately forty-five (45) degrees relative to its longitudinal axis to receive and accommodate diagonally positioned primary tie system **1298**, however alternate angles may be substituted without departing from the scope hereof. Lower plate **1245** is also substantially rectangular and made of a rigid material such as, but not limited to,  $\frac{1}{2}$ -inch thick steel and having dimensions of two and one sixteenth ( $2\frac{1}{16}$ ) inches wide and seven and one quarter ( $7\frac{1}{4}$ ) inches long. In the depicted embodiment, lower plate **1245** is bent at an angle of approximately twenty-two and one half ( $22\frac{1}{2}$ ) degrees from its longitudinal axis to receive and accommodate the position of secondary tie system **1252**, which in the depicted embodiment is a secondary support rod. However alternate angles may be substituted without departing from the scope hereof.

[0141] As seen in the top view of FIG. 10I, upper plate **1246** includes an aperture **1284** at its proximal end. As seen in FIG. 10F, similarly, lower plate **1245** includes an aperture **1288** at its proximal end. In the depicted embodiment, as seen in FIG. 10B, rod insert **1250b** is connected to a distal end of upper plate **1246** by means of a fillet weld, and rod insert **1241** is connected to a distal end of lower plate **1245** by means of a fillet weld.

[0142] Primary support **1253** is coupled to structural member **302** by means of fastener **1251**. In the depicted embodiment, fastener **1251** is a threaded shear stud being made of a rigid material such as steel and the like welded to structural member **302**. The apertures of upper and lower plates **1246** and **1245**, respectively, are passed over the stud and a nut compatible with the threaded end of the stud is fastened atop upper plate **1246** to hold primary support **1253** in place relative to structural member **302** therewith. However, alternate sizes for upper bent plate **1246** and lower bent plate **1245**, and alternate methods of attaching such plates to the

structural member **302**, to rod insert **1250b**, and to each other may be substituted without departing from the scope hereof.

[0143] In the depicted embodiment, secondary tie system **1252** may be a coil rod similar to rod **1249** of primary tie system **1298**, however, alternate ties or supports may be substituted.

[0144] In the depicted embodiment, as shown in FIG. 10F, secondary support **1254** is substantially rectangular, made of a rigid metal such as steel and has two apertures **1288** and **1290** at either end. In the depicted embodiment, secondary support **1254** is bent at an angle of approximately twenty-two and one half ( $22\frac{1}{2}$ ) degrees from its longitudinal axis to receive and accommodate the position of secondary tie system **1252**, however alternate angles may be substituted without departing from the scope hereof.

[0145] Secondary support **1254** is coupled to the upwardly facing surface **1008** of horizontal member **1004** via a fastener **1292** passing through aperture **1288** and into insert **1202c**. For example, fastener **1292** may be a one half ( $\frac{1}{2}$ ) inch diameter bolt.

[0146] Secondary tie system **1252** is attached at a first end by insertion and/or threading of secondary tie system into rod insert **1241**. The second end of secondary tie system **1252** is passed through an aperture **1290** in secondary support **1254** and a retention mechanism **1292** is threaded onto the second end of secondary tie system **1252** until it is in contact with secondary support **1254**, thereby holding secondary tie system **1252** in place. Retention mechanism may be a nut or the like.

[0147] Although the depicted attachment mechanism **1060** includes, primary support **1253**, secondary support **1254**, primary tie system **1298**, and secondary tie system **1252**, alternate attachment mechanisms **1060** are envisioned. For example, secondary support **1254** and secondary tie system **1252** may be omitted. Or, primary support **1253** and primary tie system **1298** may be omitted. Alternatively, various components of the attachment mechanism **1060** may be substituted for other components having equivalent functionality. And alternate methods of coupling the components of attachment mechanism **1060** may be substituted without departing from the scope hereof.

[0148] After form **1000** is tied in place, it contains the work area as soon as it is installed as discussed, which minimizes or eliminates fall hazards, thereby eliminating the time, costs (e.g., labor costs, removal costs, disposal costs, etc.), and downtime associated with installation of safety measures that are typically required (e.g., formwork, scaffolding, road closure, etc.) to contain the work area. The exposed ties having a load rating well-over that required to temporarily anchor fall protection life lines. Minimal or zero excess materials are needed to contain the work area since the form performs this task while also remaining in place after construction to become part of the structure being built. Also, the disruption of traffic or other environmental considerations beneath the structure being built is minimized as all work can be safely performed from atop the structure.

[0149] After the form **1000** is installed as depicted in FIG. 10C, the process of installing the deck and barrier may proceed as described above with respect to FIGS. 3A through 3I with the following modifications.

[0150] After the concrete is poured and cured, the portion of attachment mechanism **1060** located above the deck which is not going to be encased in the barrier may optionally be removed from the form **1000** via dismantling turn-

buckle with jaw ends **1251** from form attachment **1206a** on one end and rod insert **1250a** on the opposite end. The rod insert **1250a** and form attachment **1206a** may need to be cut away from the newly formed deck by means of a grinder and the like. Alternatively, they may be left in place and encased in the overall deck and barrier combination. The encasement of form **1000** facilitates the ability of form **1000** to accommodate the shear and moment forces placed thereupon by the weight of the overall deck and barrier.

[0151] Referring now to FIG. 10J, depicted is an enlarged side view of the distal end of the horizontal component of the form of FIG. 10A having an alternate distal end in which the upwardly facing surface **1008** angles upwardly as it extends outwardly and away from joining component **1210** at a greater angle than that shown in FIGS. 10A through 10I. By angling the height of upwardly facing surface **1008** at a greater angle relative to joining component **1210**, the thickness of the distal end of horizontal component **1004** is increased as compared to the distal end of the horizontal component shown in FIGS. 10A through 10I. A thicker distal end may be desirable, for example, when a structural support such as structural support **1302** has a varied flange thickness (i.e., the bottom of the top flange remains constant while the top of the flange steps up or down). Since standard construction practice is to hold the bottom of form **1000** even with the bottom of the top flange, the edge of the form **1000** needs to be thickened so that the notch can be blocked out during casting in essence putting a step in form **1000** along its edge to mimic the geometry of the structural support **1302** while maintaining at least one and a half inches (1½") of concrete cover above the notch area to take the load. FIG. 10J depicts one method of accounting for such concrete cover. Another example is shown in FIG. 10K in which the distal end is thickened but, in lieu of a continuously upwardly angled slope to upwardly facing surface **1008**, form **1000** includes a transitional surface **1062** that transitions from the upwardly facing surface **1008** of the thickened distal end to the area proximal to the thickened end at an angle of approximately forty five degrees. In this manner, the distal end of horizontal component **1004** is thickened while maintaining the proximal portion of horizontal component at a thickness more similar to that of the joining component **1210** interface. However, alternate methods of thickening the distal end of horizontal component **1004** may be substituted without departing from the scope hereof.

[0152] Turning now to FIGS. 11A through 11F, depicted is yet another exemplary alternate stay-in-place form **11000** in accordance with an alternate embodiment of the present invention, the form mounted parallel to, and tied atop, a concrete structural member **11102** having a substantially rectangular cross-section. This exemplary form **11000** is utilized as a form for supporting uncured concrete, and, after the concrete has cured, form **11000** remains an integral part of the structure formed thereby. This exemplary form **11000** is intended for uses similar to the uses of forms **100** and **1000**, and provides similar benefits to forms **100** and **1000**, as described in greater detail above.

[0153] Similar to form **1000**, form **11000** is a relatively thin, substantially L-shaped panel that includes vertical component **11002** and an extremely minimal horizontal component **11004**. In the depicted embodiment, vertical component **11002** is located substantially perpendicular to horizontal component **11004**, however, alternate orientations may be substituted.

[0154] Vertical component **11002** has a thickness  $T_{1100}$  of approximately two and one quarter inches (2¼"). The thickness  $T_{1101}$  of horizontal component **1104** is thicker (i.e., approximately three (3) inches), however, alternate thicknesses may be substituted without departing from the scope of the present invention.

[0155] In the depicted embodiment, the features of form **11000** including, without limitation, insert **11202**, bevel **11212**, vertical component upwardly facing surface **11222**, form inwardly facing surface **11010**, joining component inwardly facing surface **11234**, joining component **11210**, ornamental feature **11240**, downwardly facing surface **11114**, and rabbet **11218** are substantially identical to the equivalent components of form **1000**, namely, insert **1202**, bevel **1212**, upwardly facing surface **1222**, inwardly facing surface **1010**, inwardly facing surface **1234**, joining component **1210**, ornamental feature **1240**, downwardly facing surface **1114**, and rabbet **1218** as discussed above with the following exceptions.

[0156] In the depicted embodiment, as best seen in FIG. 11B, form **11000** includes a plurality of inserts **11202e** recessed in the upper edge of vertical component outwardly facing surface **11006** of vertical component **11002**. Inserts **11202e** are similar to inserts **202** as described in greater detail herein with regards to form **100**. In the depicted embodiment, as depicted in FIG. 11D, inserts **11202e** are located approximately two (2) feet from each other horizontally and approximately six (6) inches from the lateral sides of form **11000**. Inserts **11202e** facilitate the attachment of an external, removable form such as secondary form **11500** that allows the concrete barrier **11502** to be poured over the top of form **11000** as shown in FIG. 11E. Removable secondary form **11500** may be coupled to form **11000** with any form attachment **11206** compatible with insert **11202e** including, without limitation, bolts or the like. In the depicted embodiment, removable form **11500** has a substantially rectangular body **11508** with a substantially rectangular cross section as well as a lower band **11504** coupled to the bottom interior of the rectangular body. Lower band **11504** has an angled upwardly facing surface **11506** that extends upwardly at an angle of approximately forty five (45) degrees as it extends outwardly away from form **11000**. The innermost, bottommost edge of band upwardly facing surface **11506** is in contact with the outermost, bottommost edge of primary form upwardly facing surface **11222** such that a channel is formed therebetween. When this channel is filled with concrete and such concrete cures, a concrete decorative panel is formed atop the outwardly facing surface of form **11000** for aesthetic purposes. However alternately configured secondary forms and form liners may be substituted without departing from the scope hereof including, without limitation, forms of different materials and different shapes.

[0157] Similar to form **1000**, form **11000** is secured in place to concrete structural member **11102** via an attachment mechanism **11060** that includes primary supports **11253**, secondary supports **11254**, primary tie system **11298**, and secondary tie system **11252**. However, such supports vary in some manners from those utilized for form **11000**.

[0158] First, primary support **11253** utilized with form **11000** includes a single plate **11246a** only and rather than upper and lower plates. The angle of the bend in plate **11246** may be adjusted as needed to accommodate the angle at which the primary tie system **11298** will be installed. Primary support **11253** couples to concrete structural member

**11102** via insertion of a form attachment **11206f** such as a screw, bolt or the like through the aperture **11284** in plate **11246a** into the concrete structural member, or an insert placed therein, wherein the head of the screw, bolt, or the like is larger than the aperture, thereby holding plate **11246a** in place.

[0159] Primary tie system **11298** is substantially identical to primary tie system **12298**, as described with reference to FIG. 12B, however, it attaches on its upper end to form **11000** via a plate **11246b** rather than a coil loop and eye bolt style form attachment. Plate **11246b** is substantially identical to plate **11246a** and it couples to form **11000** in the same manner with which plate **11246a** couples to concrete structural member **11202**, however the angle of the bend in plate **11246b** may be adjusted to accommodate the angle of the primary tie system **11298**.

[0160] Also, secondary supports **11254** differs from secondary support **1254** as shown in FIG. 11F. Secondary support **11254** is an L shaped bracket having a base aperture **11286** that is substantially centered in base **11287** and a wall aperture **11284** that is substantially horizontally centered in wall **11285** at an upper end thereof. As also seen in FIG. 11F, secondary support is coupled to a concrete structural member **11102**, or an insert recessed therein, via a fastener or form attachment **11289** such as a bolt and washer or a screw. Secondary tie system **11252** is attached to form **11000** via passing a first end of rod **11252** through wall aperture **11284** (such that rod **11252** is substantially parallel to concrete structural member **11102**), and then threading it into an insert **11202** recessed in form **11000** as shown in FIG. 11F. Inserts **11202** are similar to those described in greater detail hereinabove with regards to inserts **202**. After such threading, secondary tie system **11252** is further coupled to secondary support **11254** via the threading of a secondary tie system fastener **11290** to a second end of secondary tie system **11252** until the fastener is in contact with an outwardly facing surface **11291** of wall **11285**. Secondary tie system fastener may be, for example, a washer and a nut as shown in FIG. 11F.

[0161] After the form **11000** is installed as depicted in FIG. 11A, the process of installing the deck and barrier may proceed as described above with respect to FIGS. 3A through 3I with the following modifications. After the deck concrete is poured and cured, the portion of attachment mechanism **11060** located above the deck and which is not going to be encased in the barrier may optionally be removed from the form **11000** via dismantling adjustable fastener **11251** from upper plate **11246** on one end and rod insert **11250a** on the opposite end. The rod insert **11250a** and upper plate **11246** may need to be cut away from the newly formed deck by means of a grinder and the like. Alternatively, they may be left in place and encased in the overall deck and barrier combination. The encasement of form **11000** facilitates the ability of form **11000** to accommodate the shear and moment forces placed thereupon by the weight of the overall deck and barrier.

[0162] Further, when the concrete for the barrier is poured, it is poured to a height that is higher than the upwardly facing surface **11222** of form **11000**, and is held in place by removable form **11508**. In this manner, the barrier is poured over form **11000**. After the concrete is cured, the removable form **11508** is then removed from the outwardly facing surface of form **11000**.

[0163] Referring next to FIGS. 12A through 12C, depicted is yet another exemplary alternate stay-in-place form **12000** in accordance with an alternate embodiment of the present invention, the form mounted parallel to, and tied atop, a structural member **302** as discussed in greater detail above. This exemplary form **12000** is utilized as a form for supporting uncured concrete for a deck only (e.g., in an embodiment in which there is a steel railing with a sidewalk or safety walk in lieu of a concrete barrier), and, after the concrete has cured, form **12000** remains an integral part of the structure formed thereby. This exemplary form **12000** is intended for uses similar to the uses of forms **100**, **1000**, and **1100**, and provides similar benefits to such forms, as described in greater detail above with the modifications described herein.

[0164] Similar to form **1000**, form **12000** is a relatively thin, substantially L-shaped panel that includes a relatively short vertical component **12102** and a longer horizontal component **12104**. In the depicted embodiment, vertical component **12102** is located substantially perpendicular to horizontal component **12104**, however, alternate orientations may be substituted.

[0165] In the depicted embodiment, the features of form **12000** including, without limitation, insert **12202**, form interior surface **12006**, bevel **12212**, vertical component upwardly facing surface **12222**, vertical component inwardly facing surface **12010**, joining component inwardly facing surface **12234**, joining component **12210**, horizontal component downwardly facing surface **12114**, and rabbet **12218** are substantially identical to the equivalent components of form **1000**, namely, insert **1202**, form interior surface **1006**, bevel **1212**, vertical component upwardly facing surface **1222**, vertical component inwardly facing surface **1010**, joining component inwardly facing surface **1234**, joining component **1210**, horizontal component downwardly facing surface **1114**, and rabbet **1218** as discussed above with the following exceptions.

[0166] In the depicted embodiment, form **12000** is mounted parallel to, and tied atop, structural member **302**. As shown in FIG. 12A, form **12000** is supported by at least one pair of L-shaped brackets **12206a** and **12206b**. Each bracket **12206** is formed from a pair of bracket sections **12208a** and **12208b**, which may be made of a rigid material such as steel or the like. Second bracket section **12208b** is oriented perpendicular to the vertical axis of structural member **302**. First bracket section **12208a** is disposed vertically at the distal end of second bracket section **12208b**, and its bottommost end is welded to the distal end of second bracket section **12208b** such that the first and second bracket sections together form a substantially ninety (90) degree angle cradle capable of holding form **12000** in place thereupon. In the depicted embodiment, the angle is ninety (90) degrees, however alternate angles may be substituted without departing from the scope hereof. Also, varying quantities of brackets and bracket sections, as well as brackets having differing configurations, may be substituted without departing from the scope hereof.

[0167] Brackets **12206** are connected to structural member **302** and form **12000** via attachment mechanism **12060**. In the depicted embodiment, attachment mechanism **12060** is substantially identical to attachment mechanism **1060** as described above with the exception of the primary tie system **12298**. As best seen in FIG. 12B, primary tie system **12298** includes two threaded rods **12249a** and **12249b** (e.g., inline,

Dayton Superior threaded metal rods having a  $\frac{3}{4}$ -inch diameter capable of withstanding a load of at least 18,000 lbs), which are coupled to substantially vertical first bracket section **12208a** and structural member **302** in a diagonal fashion.

[0168] A first rod **12249a** has a first threaded end that is connected to apertures in substantially vertical first bracket section **12208a** by means of fastener **12210**. In the depicted embodiment, fastener **12210** is a washer and coil nut, however, alternate fasteners may be substituted without departing from the scope hereof. A second end of first rod **12249a** is connected to a first end of second rod **12249b** via an adjustable fastener **12250**. In the depicted embodiment, adjustable fastener **12250** is a cylinder-shaped, strut coil tie with a  $\frac{3}{4}$ -inch diameter and six-inch length. Adjustable fastener **12250** allows the spacing between rods **12249a** and **12249b** to be adjusted via rotation of adjustable fastener **12250** in either of two directions, typically via a wrench. The adjustable fastener facilitates placing the form **12000** in a substantially plumb position. A second end of second rod **12249b** is coupled to a coil loop **12251**, which is welded to upper plate **12246** in the same manner discussed above with respect to upper plate **1246** as shown in FIG. 10B.

[0169] Another difference in the form **12000** as compared to form **1000** is that the horizontal component **12104** includes horizontal component apertures **12502** in lieu of inserts **1202c**. These apertures **12500** allow secondary support **12254** to be coupled to horizontal member **12104** and second bracket section **12208b** via passage of a fastener **12503** (e.g., a bolt with a washer) through secondary support aperture **12500**, horizontal component aperture **12502**, and second bracket section aperture **12504** to connect all three components to each other, sandwiching form **12000** between secondary support **12254** and second bracket section **12208b**. In some embodiments, the fastener **12502** is configured to receive a hollow plastic sleeve **12240** to create a small tunnel to allow access to the fastener **12503** after the poured deck cures.

[0170] Additionally, as seen in FIG. 12C, another variation of form **12000** is that a channel **12216** is substituted in lieu of a protrusion **216** as discussed above with respect to form **100**. As best seen in FIG. 12C, channel **12216** is recessed longitudinally along the length of form **12000** directly below joining component **12234**. Channel **12216** has a substantially triangular cross-section, with both internal sides oriented at an angle of forty five (45) degrees relative to the vertical midpoint of the channel. Channel **12216** acts as a drip strip to cause water to drip downward rather than along downwardly facing surface **12114**. Channel **12216** and bevel **12212** both act to eliminate or minimize the amount of water that reaches structural support **302** in an effort to minimize corrosion thereof. However, alternate configurations, locations, and/or shapes for this channel may be substituted, or channel **12216** may be omitted, without departing from the scope hereof.

[0171] After the form **12000** is installed as depicted in FIGS. 12A and 12B, the process of installing the deck may proceed as described above with respect to FIGS. 3A through 3I (except that no barrier is poured). After the deck concrete is poured and cured, the portion of attachment mechanism **12060** located above the deck and which is not going to be encased in the deck may be removed from the form **12000** via dismantling adjustable fastener **12250** from its adjacent rods **12249a** and **12249b**. The rods **12249a**

and/or **12249b** may need to be cut away from the newly formed deck by means of a grinder and the like. Additionally, the brackets **12206** are removed from form **12000**, the latter remaining in place internal to the poured deck. The encasement of form **12000** in the poured deck facilitates the ability of form **12000** to accommodate the shear and moment forces placed thereupon by the weight of the overall deck.

[0172] Turning now to FIGS. 13A through 13F, depicted is an exemplary alternate stay-in-place fascia form **13000** in accordance with one alternate embodiment of the present invention, the form mounted parallel to, and tied atop, structural member **302**. This exemplary form **13000** is utilized as a form for supporting uncured concrete, and, after the concrete has cured, form **13000** remains an integral part of the structure formed thereby. This exemplary form **13000** is intended for uses similar to the uses of the other forms discussed herein, and provides similar benefits to such forms, as described in greater detail above.

[0173] Similar to form **100**, form **13000** is a relatively thin, substantially L-shaped panel that includes vertical component **13002** and horizontal component **13004**. In the depicted embodiment, vertical component **13002** is located substantially perpendicular to horizontal component **13004**, however, alternate orientations may be substituted.

[0174] Vertical component **13002** and the proximal portion of horizontal component **13004** have thicknesses similar to the thicknesses of form **1000** as discussed in greater detail above. The height  $H_{13}$  and width  $W_{13}$  of form **13000** is approximately forty eight inches (48"), and the length  $L_{13}$  is approximately sixty inches (60"), however, varied dimensions may be substituted to accommodate, for example, desired size of the structure being built as well as material strength and geometric boundaries.

[0175] In the depicted embodiment, the features of form **13000** including, without limitation, insert **13202**, form attachment **13206**, form interior surface **13006**, bevel **13212**, vertical component upwardly facing surface **13222**, vertical component inwardly facing surface **13010**, joining component inwardly facing surface **13234**, joining component **13210**, horizontal component downwardly facing surface **13114**, and rabbet **13218** are substantially identical to the equivalent components of form **1000**, namely, insert **1202**, form attachment **1206**, form interior surface **1006**, bevel **1212**, vertical component upwardly facing surface **1222**, vertical component inwardly facing surface **1010**, joining component inwardly facing surface **1234**, joining component **1210**, horizontal component downwardly facing surface **1114**, and rabbet **1218** as discussed above with the exceptions of the attachment mechanism **13060**.

[0176] The attachment mechanism **13060** depicted in FIGS. 13A-13C may be used, for example, with large forms that have large overhangs relative to structural member **302** due to factors including, but not limited to, the size of horizontal component **13004**. In the depicted embodiment, attachment mechanism **13060** incorporates a strut style secondary tie system **13252** to help reduce and distribute the stress placed on the form **13000**.

[0177] As depicted in FIGS. 13A and 13B, each form **13000** incorporates a pair of attachment mechanisms **13060** for coupling form **13000** to structural member **302**. Further, each attachment mechanism **13060** includes primary support **13253**, secondary support **13254**, primary tie system **13298**, and secondary tie system **13252**. Primary tie system **13298**

includes a pair of threaded tie back rods **13282** installed diagonally, made of a rigid material such as steel, and sized for a load of, for example, at least 95,000 lbs. A first end of primary tie system **13298** is coupled to form **13000** via insert **13202** and a form attachment **13206** such as an eyebolt, anchor rod or the like. Insert **13202** and form attachment **13206** at a point above the vertical midpoint of vertical component **13002**. A second end of primary tie system **13298** is attached to structural support **302** via a pair of primary supports **13253**.

[0178] In the depicted embodiment, primary support **13253** includes a primary fastener **13284**, plate **13285**, plate body fastener **13287**, and plate base fastener **13286**. As shown in FIG. 13C, the second end of each primary support **13253** is coupled to a respective primary fastener **13284**. In the depicted embodiment, primary fastener **13284** is a clevis constructed of a one half ( $\frac{1}{2}$ ) inch rigid material such as Grade 50 steel and the like with an aperture **13297** having a diameter of seven eighths ( $\frac{7}{8}$ ) inch. The primary fastener **13284** has a threaded aperture **13288** for engaging the threaded end of the respective tie back rod **13282**. The tie back rod **13282** and primary fastener **13284** connect to existing structural member **302** by means of a rectangular, bent plate **13285** with a length of nine and one quarter ( $9\frac{1}{4}$ ) inches, a width of four (4) inches, and a thickness of one half ( $\frac{1}{2}$ ) inch. However, the dimensions of plate **13285** may vary depending upon, for example, the governmental standard being met (e.g., OSHA 4:1 Failure (ULT), AASHTO ASD and 2:1 (ULT), AISC ASD AND 2:1 (ULT)). Plate **13285** is made of a rigid material such as Grade 50 steel and the like and has base and body apertures **13298** and **13299**, respectively. In the depicted embodiment, the body **13400** of plate **13285** is bent at an angle  $A_1$  of approximately twenty-five (25) degrees relative to the longitudinal axis of body **13400** of plate **13285**. Also, base **13402** has a length  $L_{11}$  of approximately three and one quarter ( $3\frac{1}{4}$ ) inches, and the body **13400** has a length  $L_{12}$  of approximately four and a quarter ( $4\frac{1}{4}$ ) inches with a bend length  $L_{13}$  of approximately one and three quarters ( $1\frac{3}{4}$ ) inch, however, alternate angles, lengths, and/or other dimensions may be substituted to accommodate, for example, varying sizes of forms.

[0179] Plate **13285** is coupled to structural member **302** via sliding base aperture **13298** of plate **13285** over a seven-eighths ( $\frac{7}{8}$ ) inch threaded shear stud welded to the structural member **302**. A nut is then threaded over the stud until it contacts the upwardly facing surface of the base of plate **13285** in order to secure the plate **13285** to the structural member **302**.

[0180] Also, the clevis **13284** is slid over the body of plate **13285** until its apertures **13297** align with body aperture **13299** of plate **13285**. Thereafter, fastener **13287** is passed therethrough to couple primary fastener **13284** and the coupled primary support to plate **13285**. In this manner, each tie back rod **13282** is coupled to structural member **302**. Fastener **13287** is in the form of a clevis bolt and respective nut, however, alternate fasteners may be substituted.

[0181] Thereafter, or prior to such attachment, secondary tie system **13252** may be installed. In the depicted embodiment, secondary tie system includes a strut such as an interior angle strut, which may be installed via a form attachment coupled to an insert as described in greater detail herein. Or, in some instances, screws or the like may be drilled directly into form **13000**.

[0182] Turning now to FIG. 13D, depicted is an alternate primary support **13653**, which includes a primary fastener **13684**, plate **13685**, and plate base fastener **13686**. As shown in FIG. 13D, the second end of each primary support **13653** is coupled to a respective primary fastener **13684**. In the depicted embodiment, primary fastener **13684** is a seven-eighths inch ( $\frac{7}{8}$ " diameter by two and one half inches ( $2\frac{1}{2}$ " long coupler nut which is welded to plate **13685**. The primary fastener **13684** has a threaded aperture **13688** for engaging the threaded end of the respective tie back rod **13282**. Fastener **13684** is in the form of a coupler nut welded to plate **13685**, however, alternate fasteners may be substituted.

[0183] The tie back rod **13282** and primary fastener **13684** connect to existing structural member **302** by means of a rectangular, bent plate **13685** with a length of nine and one quarter ( $9\frac{1}{4}$ ) inches, a width ranging from three inches (3") to four and three quarters inches ( $4\frac{3}{4}$ "), and a thickness of one (1) inch. However, the dimensions of plate **13685** may vary depending upon, for example, the governmental standard being met (e.g., OSHA 4:1 Failure (ULT), AASHTO ASD and 2:1 (ULT), AISC ASD AND 2:1 (ULT)). The plate **13685** is made of a rigid material such as Grade 50 steel and the like and has base aperture **13698**. In the depicted embodiment, the body **13600** of plate **13685** is bent at an angle  $A_1$  of approximately twenty-five (25) degrees relative to the longitudinal axis of base **13602** of plate **13685**. Also, base **13602** has a length  $L_{11}$  of approximately three and three eighths ( $3\frac{3}{8}$ ) inches, and the body **13600** has a length  $L_{12}$  of approximately three and one sixteenth ( $3\frac{1}{16}$ ) inches with a bend length  $L_{13}$  of approximately one and three quarters ( $1\frac{3}{4}$ ) inch, however, alternate angles, lengths, and/or other dimensions may be substituted to accommodate, for example, varying sizes of forms.

[0184] Plate **13685** is coupled to structural member **302** via sliding base aperture **13698** of plate **13685** over a seven-eighths ( $\frac{7}{8}$ ) inch threaded shear stud welded to the structural member **302**. A nut is then threaded over the stud until it contacts the upwardly facing surface of the base of plate **13685** in order to secure the plate to the structural member **302**.

[0185] It should be noted that although FIG. 13D depicts a single plate **13685** with a first angle  $A_1$ , it is envisioned that multiple plates could be stacked and each plate could have varying dimensions and/or angles to allow each of the plates to be coupled to respective tie back rods or the like similar to the stacked plates shown in FIG. 10B, as discussed above, but having the features of fastener **13653**.

[0186] Referring now to FIG. 13E, depicted is an alternate primary support **13853**, which includes a primary fastener **13884**, plate **13885**, secondary fastener **13887**, and plate base fastener **13886**. As shown in FIG. 13D, the second end of each primary support **13853** is coupled to a respective primary fastener **13884** and secondary fastener **13887**. In the depicted embodiment, primary fastener **13884** and secondary fastener **13887** are seven-eighths inch ( $\frac{7}{8}$ " diameter by two and one half inches ( $2\frac{1}{2}$ " long coupler nuts which are welded to plate **13885**. The primary fastener **13684** has a threaded aperture **13888** for engaging the threaded end of a primary tie back rod **13282**, and the secondary fastener **13887** has a threaded aperture **13889** for engaging the threaded end of a secondary tie back rod **13252**. Although fasteners **13884** and **13887** are in the form of welded coupler nuts, alternate fasteners may be substituted.

[0187] The tie back rod **13282**/primary fastener **13884** and the tie back rod **13252**/secondary fastener **13887** connect to existing structural member **302** by means of a rectangular, bent plate **13885** with a length of approximately thirteen (13) inches, a width ranging from three inches (3") to four and three quarters inches (4¾"), and a thickness of one (1) inch. However, the dimensions of plate **13885** may vary depending upon, for example, the governmental standard being met (e.g., OSHA 4:1 Failure (ULT), AASHTO ASD and 2:1 (ULT), AISC ASD AND 2:1 (ULT)). The plate **13685** is made of a rigid material such as Grade 50 steel and the like and has base aperture **13898**. In the depicted embodiment, the body **13800** of plate **13885** is bent at two angles A1 and A2. Angle A<sub>1</sub> is approximately forty-five (45) degrees relative to the longitudinal axis of base **13802** of plate **13885**, and angle A<sub>2</sub> is approximately twenty-five (25) degrees relative to the longitudinal axis of body **13800** of plate **13885**. As depicted in FIG. 13E, primary fastener **13884** is welded to the upwardly facing surface **13890** of the body **13800** and secondary fastener **13887** is welded to the downwardly facing surface **13891** of the distal end of plate **13885**. However, alternate angles, lengths, and/or other dimensions may be substituted to accommodate, for example, varying sizes of forms.

[0188] Plate **13885** is coupled to structural member **302** via sliding base aperture **13898** of plate **13885** over a seven-eighths (7/8) inch threaded shear stud welded to the structural member **302**. A nut is then threaded over the stud until it contacts the upwardly facing surface of the base of plate **13885** in order to secure the plate to the structural member **13302**.

[0189] Further, alternate attachment mechanisms **13060** may be substituted without departing from the scope hereof. Or, alternate components of the attachment mechanism **13060** including, but not limited to, primary support **13253**, secondary support **13254**, primary tie system **13298**, and secondary tie system **13252** may be substituted without departing from the scope hereof.

[0190] Turning now to FIG. 13F, depicted is an alternate primary support **14253**, which includes a primary fastener **14684**, plate **14400**, tie system fastener **14406**, and plate fastener **14402**. This type of support may be used, for example, when a vertical support is available (e.g., rebar or a shear stud) to which the plate **14400** may be attached.

[0191] As shown in FIG. 13F, in the depicted embodiment, primary fastener **14684** includes a tie system fastener **14406** that includes a bolt and nut combination. Eyebolt **14408** includes a threaded aperture **14688** in a first end for engaging the threaded end of the respective tie back rod **13282**. Eyebolt **14408** is held to plate **14400** via tie system fastener **14406**, the bolt of which passes through the head of the eyebolt **14408** and corresponding apertures in the plate **14400**. The bolt is held in place via the tightening of the nut on the end of the bolt external to plate **14400**. However, tie back rod **13282** may be coupled to plate **14400** via alternate fasteners without departing from the scope of the present invention.

[0192] Primary support **14253** connects to a vertical support **13286** coupled to the structural member **302** by means of a cam-locking U-shaped bracket **14400**. That is, the U-shaped plate includes a bite bit cam **14402** that bites into the vertical support **13286** when the plate and its associated cam are rotated relative to vertical support to create a

clamping force on the vertical support. This clamping force prevents or minimizes movement of plate **14253** relative to vertical support **13286**.

[0193] In an alternative embodiment, primary support **14253** is rotated one hundred and eighty degrees prior to attachment to the vertical support. And, optionally, a sleeve **14410** may be included within plate **14400** to further prevent or minimize movement of plate **14253** relative to vertical support **13286**. Alternate embodiments are also envisioned in which one or more bolt and nut (and optionally washer) combinations are utilized to squeeze the U shaped plate around the vertical support. In any of the above described embodiments, embodiments are also envisioned in which the primary support **14253** is allowed to ride up (i.e., move vertically) the vertical support until a head or other interference limits movement thereof.

[0194] In embodiments of the present invention utilizing primary supports such as primary support **14253**, the primary support is typically coupled to the vertical support prior to installation of the corresponding form. Next, the form, which has the tie rods pre-installed on it, is lifted into place. Next, the tie rods are coupled to primary support **14253**. Although other sequences can be substituted. For example, the primary support **14253** could be installed at the same time the form is lifted into place and/or the tie rods could be installed after the form is lifted into place.

[0195] It will be appreciated by those skilled in the art that changes could be made to the embodiments described above without departing from the broad inventive concept thereof. It is understood, therefore, that this invention is not limited to the particular embodiments disclosed, but it is intended to cover modifications within the spirit and scope of the present invention as defined by the appended claims.

1. We claim a form for creation of a structure, the form for supporting uncured concrete prior to curing comprising:

a substantially vertical component, said substantially vertical component having a substantially vertical inwardly facing surface and a substantially vertical outwardly facing surface;

a substantially horizontal component having a substantially horizontal inwardly facing surface and a substantially horizontal outwardly facing surface, said substantially vertical component located substantially perpendicular to said substantially horizontal component and extending upwardly from said horizontal component, the substantially vertical component and the substantially horizontal component forming an L shape;

at least one insert in or through at least one of the group consisting of the substantially vertical inwardly facing surface, the substantially horizontal inwardly facing surface; and combinations thereof;

a rabbet extending longitudinally along the substantially horizontal component, the rabbet recessed in said substantially horizontal outwardly facing surface at the distal end thereof, the rabbet defined by top and side surfaces, the side surface being substantially vertical, and the top surface located at an angle of greater than ninety degrees relative to the side surface, the top surface tapered upwardly as it extends away from the side surface.

2. A form according to claim 1, further comprising:

at least one form attachment configured for mating with the at least one insert.



3. A form according to claim 2, wherein said at least one form attachment is an exterior reinforcement.

4. A form according to claim 1, wherein said at least one insert is threaded.

5. A form according to claim 1, wherein said interconnection clip includes at least one railing support.

6. A form according to claim 1, further comprising: at least one of the group consisting of an interior reinforcement, an ornamental feature, and combinations thereof.

7. A form according to claim 1, wherein a thickness of said substantially horizontal component and said substantially vertical component is approximately two inches.

8. A form according to claim 1, wherein an upwardly facing surface of said substantially vertical component inclines upwardly and inwardly toward said form interior surface at an angle of approximately thirty degrees.

9. A form according to claim 1, further comprising: a joining component.

10. A form according to claim 9, wherein said joining component extends at an angle of 45 degrees relative to said substantially vertical inwardly facing surface and said substantially horizontal inwardly facing surface.

11. We claim a form for creation of a structure, the form for supporting uncured concrete prior to curing comprising:

a substantially vertical component, said substantially vertical component having a substantially vertical inwardly facing surface and a substantially vertical outwardly facing surface;

a substantially horizontal component having a substantially horizontal inwardly facing surface and a substantially horizontal outwardly facing surface, said substantially vertical component located substantially perpendicular to said substantially horizontal component and extending upwardly from said horizontal component, the substantially vertical component and the substantially horizontal component forming an L shape;

at least one insert in or through at least one of the group consisting of the substantially vertical inwardly fac-

ing surface, the substantially horizontal inwardly facing surface; and combinations thereof; and

a rabbet extending longitudinally along the substantially horizontal component, the rabbet recessed in said substantially horizontal outwardly facing surface at the distal end thereof; and

a bevel extending longitudinally along the intersection of the substantially vertical outwardly facing surface and the substantially horizontal outwardly facing surface.

12. A form according to claim 11, wherein said bevel is located at an angle of 45 degrees relative to said substantially vertical outwardly facing surface and said substantially horizontal outwardly facing surface.

13. A form according to claim 1, wherein an upper corner of a distal end of said substantially horizontal component is rounded.

14. A form according to claim 1, further comprising: a protrusion extending longitudinally from said substantially horizontal outwardly facing surface.

15. A form according to claim 14, wherein the protrusion has a semicircular cross section.

16. A form according to claim 14, wherein said protrusion is located at the approximate midpoint of a proximal half of said substantially horizontal component.

17. A form according to claim 1, wherein said rabbet is substantially L-shaped.

19. A form according to claim 11, wherein an upper corner of a distal end of said substantially horizontal component is rounded.

20. A form according to claim 11, further comprising: a protrusion extending longitudinally from said substantially horizontal outwardly facing surface.

21. A form according to claim 20, wherein the protrusion has a semicircular cross section.

22. A form according to claim 20, wherein said protrusion is located at the approximate midpoint of a proximal half of said substantially horizontal component.

\* \* \* \* \*